



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁴ : G08B 13/24	A1	(11) International Publication Number: WO 87/ 04551 (43) International Publication Date: 30 July 1987 (30.07.87)
(21) International Application Number: PCT/SE87/00015 (22) International Filing Date: 16 January 1987 (16.01.87) (31) Priority Application Number: 8600258-1 (32) Priority Date: 21 January 1986 (21.01.86) (33) Priority Country: SE (71) Applicant (for all designated States except US): INTER-MODULATION AND SAFETY SYSTEM AB [SE/SE]; Box 563, S-175 26 Järfälla (SE). (72) Inventor; and (75) Inventor/Applicant (for US only) : ÅSBRINK, Leif [SE/SE]; Pl. 8495, S-643 00 Vingåker (SE). (74) Agent: ÖRTENBLAD, Bertil; Noréns Patenbyrå AB, Banérgatan 73, S-115 26 Stockholm (SE).		(81) Designated States: AU, BR, DK, FI, JP, KR, NO, US. Published <i>With international search report.</i>

(54) Title: RECEIVING DEVICE



(57) Abstract

A receiving device for detecting the presence of an indicating device in a restricted investigation zone, where coils and associated feed and receiving equipment are provided to emit and receive magnetic alternating fields in order thereby to detect the presence of an indicating device in the investigation zone, which indicating device is capable to receive alternating fields and to re-emit an alternating field. Said receiving coils for receiving said re-emitted alternating field comprise at least two coil sets (10, 10', 10''), each of which constitutes a so-called balanced coil wound to a configuration corresponding to two substantially rectangular eights located to the side of each other in the same plane. The coil sets (10, 10', 10'') are located in parallel with each other, preferably in the same plane, where each of the coil sets (10, 10', 10'') is offset, relative to an adjacent coil set, in a direction in parallel with said plane through a distance corresponding to about one fourth of the distance (2a) in the offset direction between the outer opposed sides (18, 11; 14, 15) in a coil set (10).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	ML	Mali
AU	Australia	GA	Gabon	MR	Mauritania
BB	Barbados	GB	United Kingdom	MW	Malawi
BE	Belgium	HU	Hungary	NL	Netherlands
BG	Bulgaria	IT	Italy	NO	Norway
BJ	Benin	JP	Japan	RO	Romania
BR	Brazil	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Central African Republic	KR	Republic of Korea	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
DE	Germany, Federal Republic of	LU	Luxembourg	TD	Chad
DK	Denmark	MC	Monaco	TG	Togo
FI	Finland	MG	Madagascar	US	United States of America

WO 87/04551

PCT/SE87/00015

1

Receiving device

This invention relates to a receiving device for receiving a magnetic field in connection with a goods monitoring system.

- 5 In SE-PS 8404691-1 a system for detecting the presence of indicating devices is described which have the form, for example, of a narrow and thin, but relatively long strip of a highly permeable material, such as being commercially available under the name Permalloy. The presence of
10 such strips is detected by means of coils, which emit and receive magnetic fields, and by means of devices for the detection of signals received.

When such a strip is exposed to a relatively weak external magnetic field, it assumes in its longitudinal direction a magnetic flux density, the magnitude of which can
15 be twentythousand times higher than in the external magnetic field. The presence of such strips is detected by a detector device, in which variations in voltage induced in a receiver coil are detected.

- 20 According to said patent, two coils are caused to emit a magnetic alternating field of high frequency, where a first one of the coils emits an alternating field with a frequency, which is different from the frequency of the field emitted by the second one of the coils, and where at least
25 one difference and/or sum frequency $n \cdot f_1 + m \cdot f_2$ arising by intermodulation by the indicating device, where n and m are positive or negative integers, is caused to be received by one or several coils. According to the patent, a third magnetic alternating field of low frequency is
30 caused to be emitted in said zone. which has a frequency substantially lower than said frequencies f_1, f_2 , where the low-frequency field is caused to have a field intensity sufficiently high for, independently of the fields with the frequencies f_1 and f_2 , putting the indicating
35 device into saturated condition in step with the frequency

WO 87/04551

PCT/SE87/00015

2

of the low-frequency field. A field re-emitted from the indicating device is caused to be detected by means of a detector device as an intermodulation, occurring periodically with the frequency of the low-frequency field, between the frequencies f_1 and f_2 .

One problem with known theft-prevention systems is that the orientation of the strip in the space is of great importance for whether or not the presence of the strip in the investigation zone will be detected and, thus, whether or not alarm will be sounded. This problem normally has been solved in such a way, that emitting and receiving coils were positioned in different places relative to the investigation zone.

Another problem is that a simple receiving coil is relatively sensitive to interferences of various kind, originating from other electric devices installed in shop premises.

The present invention provides a solution of the aforesaid problems. The present invention comprises receiving coils so arranged, that indication of the presence of a strip in the investigation zone substantially takes place independently of the orientation of the strip in the space, and so arranged that they are insensitive to external interferences.

This implies that the number of expected false alarms is reduced, which is of utmost importance for a goods monitoring system of the kind here concerned.

The present invention, thus, relates to a receiving device for detecting the presence of an indicating device in a restricted investigation zone, where coils and associated feeding and receiving equipment are provided for emitting and receiving magnetic alternating fields, in order thereby to detect the presence of an indicating device in the investigation zone, which indicating device is capable to receive alternating fields and to re-emit an alternating field. The invention is characterized in that said receiv-

WO 87/04551

PCT/SE87/00015

3

ing coils, which are provided to receive said re-emitted alternating fields, comprise at least two coil sets, where each coil set is a so-called balanced coil wound to a configuration corresponding to two substantially
5 rectangular eights located to the side of each other in the same plane, and that said coil sets are located in parallel with each other, preferably in the same plane, where each of the coil sets is offset, relative to an adjacent coil set, in a direction in parallel with said
10 plane through a distance corresponding to about one fourth of the distance in the offset direction between the outer opposed sides in a coil set.

The invention is described in greater detail in the following, with reference to an embodiment thereof shown in
15 accompanying drawings and elucidating sketches, in which Fig. 1 shows schematically a coil, which is utilized according to the invention, and indicates different transport directions A-E for an indicating device in the form of said strip, Fig. 2 shows a co-ordinate system, in which the
20 coil in Fig. 1 is located in the x-y plane, Fig. 3 shows a strip oriented in the x-direction, y-direction and z-direction, respectively, Figs. 4a-4f show schematically the signal intensity (v), which is obtained at the passage of a strip past the coil in Fig. 1, depending on the orientation of the strip (x;y;z) and transport path (A-E),
25 Fig. 5 is an elucidating Figure to illustrate a coil set comprising three coils according to Fig. 1, Fig. 6 shows a monitoring zone, and Fig. 7 shows schematically a complete device for indicating the presence of an indicating
30 device in an investigation zone.

In Fig. 7 a device for detecting the presence of an indicating device is shown schematically, which indicating device, for example, has the form of a strip of a highly permeable material and is located in a restricted investigation zone 1, which is defined by two parallel screens 2,3,
35 which comprise coils for emitting and receiving magnetic

WO 87/04551

PCT/SE87/00015

4

alternating fields. A feeding device 4 is provided for emitting a field of a certain frequency by means of emitting coils. The indicating device 5 is provided to receive said fields and to re-emit an alternating field, which comprises a frequency other than that of the emitted frequency. A receiving equipment is provided for receiving a signal arising in the receiving coils due to the alternating field re-emitted by the indicating device.

The receiving equipment 6 comprises a receiver 7 and a detector circuit 8 capable to detect and interpret the signal received. When the detector circuit 8 receives a signal, which agrees with the criterion or criteria applying when an indicating device is present in the investigation zone, the detector circuit 8 emits a signal to an alarming device 9 of known kind. The system described above can be similar to that described in said Swedish patent. The present invention, however, can be used at an indicating device of a different kind, for example an indicating device in the form of a resonance circuit.

According to the present invention, the receiving coils are designed in a special way. According to the invention, the receiving coils comprise at least two coil sets, as described below. In Fig. 5 three coil sets are shown, where a first one 10 is shown by fully drawn lines, a second one 10' is shown by dash-dotted lines, and a third one 10" by dashed lines.

In Fig. 1 a coil set 10 is shown in greater detail. The coil set 10 is a so-called balanced coil wound to a configuration corresponding to two substantially rectangular eights, which are located to the side of each other in the same plane. As appears from Fig. 1, the coil set 10 has such a configuration, that the outer winding portions 11-18 form a rectangle, and the remaining winding portions 19-22 divide the rectangle into four smaller rectangles of equal size.

WO 87/04551

PCT/SE87/00015

5

The coil set 10 is wound so that from one pole 23 of it the conductor extends to the second pole 24 via the winding portions as follows: 11,19,20,12,11,19, 20,13,14,21, 20,13,14,21,22,16,15, 21,22, 16,15, 21,22, 17,18,19, 22, 5 17, 18,19,20, 12. The winding portions 11-18, thus, comprise two turns, and the winding portions 19-22 comprise four turns. The coil portions, thus, which are constituted by said smaller rectangles are wound so, that the rectangles in the first and third quadrant are wound in the same 10 direction while the rectangles in the second and fourth quadrant are wound in opposite directions.

In Fig. 3 an indicating device is shown, which has the form of a strip of a highly permeable material in three different orientations x,y and z according to the co-ordinate 15 system in Fig. 2. In the following reasoning the coil set 10 is assumed to be located in the x-y plane.

The letters A-E indicate five different imagined transport paths for a strip 5 when it is transported in the x-y plane past the coil set 10. A, thus, implies that the strip is 20 transported along the winding portions 18 and 1. B implies, that the strip is transported along a path located centrally between the winding portions 18, 11 and, respectively, 22, 20. C-E have a corresponding meaning.

The dimensions of the strip 5 are only, for example, 25 x 25 2 x 0.1 mm while the coil set can have outer dimensions of, for example, 100 x 80 cm.

In Figs. 4a-4f the signal intensity (v) is illustrated, which is obtained when a strip 5 is moved in the x-direction according to the paths A-E. At each diagram both the 30 transport path (PATH) and the orientation (ORIENT) of the strip are indicated. In Fig. 4a, thus, the signal (v) is shown which is received when the strip is x-oriented and follows the path A in Fig. 1. The indication "-E" implies, that a signal corresponding to the one shown, but with 35 opposite sign, is received when the strip is x-oriented and follows the path E. The Figs. 4b-4f show in a corres-

WO 87/04551

PCT/SE87/00015

6

ponding way the signal for different orientations of the strip when it follows different paths.

When the strip is x-oriented or z-oriented, no signal or only a very weak one is received when the strip follows the path C. When the strip is y-oriented, no signal or a very weak one is received when the strip follows one of the paths B or D.

According to the present invention, therefore, the receiving device comprises at least two coil sets 10, 10', of the kind shown in Fig. 1, where each coil set 10, 10', 10" is a balanced coil wound to a configuration corresponding to two substantially rectangular eights located to the side of each other in the same plane. The coil sets 10, 10', 10" are located in parallel with each other and preferably in the same plane. Each of the coil sets is offset, relative to an adjacent coil set, in a direction in parallel with said plane through a distance (a/-) corresponding to about one fourth of the distance (2a) in the offset direction between the outer opposed sides 18,11;14,15 in a coil set 10.

It is hereby obtained, that the paths A-E of the second coil set 10' are offset relative to the paths A-E of the first coil set. Thus, the path B of the coil 10 corresponds to the path A of the coil 10'; the path C of the coil 10 corresponds to the path B of the coil 10', a.s.o. This implies, that a signal (v) is received from one or the other or from both of the coil sets 10, 10', irrespective of which orientation the strip has and which path it follows.

It is obvious that between the paths indicated as well as at an orientation of the strip in a direction between the x-,y-z-directions a signal will be received in a corresponding way.

According to a preferred embodiment, each coil set partially overlaps an adjacent coil set, so that two respective

WO 87/04551

PCT/SE87/00015

7

opposed winding portions 16,17; 12,13, and 25,26; 27,28, respectively, of each of the coil sets 10, 10' are located along two respective straight lines, i.e. as illustrated in Fig. 5.

5 According to another preferred embodiment, a set of receiving coils comprises at least four coil sets in a vertical plane where they are offset relative to each other in the way stated above in a vertical plane, and where the total height of the coil sets exceeds 1,5 meters, preferably 1,7 meters, and the total width of the coil sets exceeds 0,5 m and preferably is about 0.8 m. A vertical screen 2;3 of such design is shown in Fig. 6.

10 In the embodiment shown in Fig. 6, the uppermost located coil set extends from the indicated level 36 to the level 32. The winding portions according to Fig. 1 are marked in Fig. 6. In a corresponding manner, the second coil set extends between the levels 35 and 31, the third coil set between the levels 34 and 30, and the fourth coil set between the levels 33 and 29.

20 According to a further preferred embodiment, two sets of receiving coils, i.e. screens 2,3, are positioned in parallel with each other and at a distance from each other of about 0.5 to 1.0 m, as illustrated in Fig. 6, whereby a restricted investigation zone 1 is formed between the same.

25 The receiving device preferably is capable to receive alternating fields of such frequency, that the wave length is long compared to the height and width of the coil sets, especially a frequency below 100 MHz, preferably below 30 30 MHz.

This implies, that the coil sets act as fully balanced coils to interferences arising from a place located at a distance from the coils, which distance corresponds to a minimum distance of about $4a$ to $6a$, see Fig. 5. Hereby 35 so-called remote interferences, from electric devices in the premises, are effectively oppressed.

WO 87/04551

8

PCT/SE87/00015

The said coil sets are connected via conductors 37,38 to the receiver 7, where emf generated in the coils are sensed.

The said emitting coils (not shown) preferably extend
5 along the periphery 41-44; 45-48 formed by the coil sets. These emitting coils are connected via conductors 39,40 to the feed equipment 4.

According to another further preferred embodiment of the invention, the winding portions of the coil sets extend in
10 tubular portions, only five of which are marked in Fig. 6 by the numeral 49. The ends of the tubular portions are attached to each other so, that a frame is formed, which has the configuration of a grid forming a number of rectangular squares, as illustrated in Fig. 6. This embodiment
15 provides the advantage, that the staff easily can monitor persons passing the investigation zone 1.

It is obvious that the present invention eliminates in a simple way the disadvantages referred to in the introductory part.

20 The present invention, of course, can be varied in different ways without abandoning the invention idea, that at least two coil sets are used which are offset relative to each other.

The present invention, thus, must not be regarded as restrict-
25 ed to the embodiments described above, but can be varied within the scope defined in the attached claims.

WO 87/04551

PCT/SE87/00015

9

Claims

1. A receiving device for detecting the presence of an indicating device in a restricted investigation zone, where coils and associated feed and receiving equipment
5 are provided for emitting and receiving magnetic alternating fields in order thereby to detect the presence of an indicating device in the investigation zone, which indicating device is capable to receive alternating fields and to re-emit an alternating field, c h a r a c t e r i z e d
10 i n that said receiving coils, which are provided to receive said re-emitted alternating field, comprise at least two coil sets (10,10', 10"), where each coil set constitutes a so-called balanced coil wound to a configuration corresponding to two substantially rectangular
15 eights located to the side of each other in the same plane, and that said coil sets (10, 10', 10") are located in parallel with each other, preferably in the same plane, where each of the coil sets (10,10', 10") is offset, relative to an adjacent coil set, in a direction in parallel
20 with said plane through a distance corresponding to about one fourth of the distance (2a) in the offset direction between the outer opposed sides (18,11;14,15) in a coil set (10).
2. A receiving device as defined in claim 1, c h a r -
25 a c t e r i z e d i n that each of the coil sets (10,10',10") has such a configuration, that the outer winding portions (11-18) form a rectangle and the remaining winding portions (19-22) divide the rectangle into four smaller rectangles of equal size.
- 30 3. A receiving device as defined in claim 2, c h a r -
a c t e r i z e d i n that those of said smaller rectangles constituting the first and third quadrant comprise a respective coil wound in the same direction, while those
of said smaller rectangles constituting the second and
35 fourth quadrant comprise a coil wound in the opposed direction.

WO 87/04551

PCT/SE87/00015

10

4. A receiving device as defined in claim 1, 2 or 3, characterized in that each coil set (10,10', 10'') partially overlaps an adjacent coil set, and that two respective opposed outer winding portions (17,16;12,13 and, respectively, 25,26;27,28) of each of the coil sets (10,10') are located along two respective straight lines.

5. A receiving device as defined in claim 1,2,3 or 4, characterized in that one set of receiving coils (2;3) at least comprises four coil sets (10,10', 10''), which are positioned in a vertical plane and offset relative to each other in the vertical plane, where the total height of the coil sets exceeds 1.5 m and preferably is about 1.7 m, and where the total width of the coil sets exceeds 0.5 m and preferably is about 0.8 m.

6. A receiving device as defined in claim 5, characterized in that two sets of receiving coils (2;3) are located in parallel with each other and at a distance from each other of about 0.5 m to 1.0 m to form a restricted investigation zone.

7. A receiving device as defined in claim 1,2,3,4,5 or 6, characterized in that it is capable to receive alternating fields of such a frequency, that its wave length is long compared to the height and width of the coil sets (10,10',10''), especially a frequency below 100 MHz, preferably below 30 MHz.






8. A receiving device as defined in claim 1,2,3,4,5,6 or 7, characterized in that said emitting coil or coils extend along the periphery (41-44; 45-48) formed by the two or more coil sets.

9. A receiving device as defined in claim 1,2,3,4,5,6, 7 or 8, characterized in that the winding portions (12-22) of the coil sets (10) extend in tubular portions (49) of a frame, and the ends of said tubular portions (49) are attached to each other so that the frame has the form of a grid where a number of rectangular squares are formed by the tubular portions.

WO 87/04551

1/2

PCT/SE87/00015



WO 87/04551

PCT/SE87/00015

2/2

Fig. 5




Fig. 6





Fig. 7



INTERNATIONAL SEARCH REPORT

International Application No PCT/SE87/00015

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) *		
According to International Patent Classification (IPC) or to both National Classification and IPC		
G 08 B 13/24 4		
II. FIELDS SEARCHED		
Minimum Documentation Searched *		
Classification System	Classification Symbols	
IPC 4 US C1	G 08 B 13/22, /24 340:571, 572, 280	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched *		
-SE, NO, DK, FI classes as above		
III. DOCUMENTS CONSIDERED TO BE RELEVANT *		
Category *	Citation of Document, ** with indication, where appropriate, of the relevant passages **	Relevant to Claim No. **
A	SE, B, 424 116 (SECURITY PRODUCTS INTERNATIONAL AS) 28 June 1982	
A	SE, B, 429 382 (KNOGO CORPORATION) 29 August 1983	
A	US, A, 4 309 697 (J.N WEAVER) 5 January 1982	
A	WO, A1, 85/03793 (INTERMODULATION AND SAFETY SYSTEM AB) 29 August 1985	
<p>* Special categories of cited documents: **</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
1987-03-17	1987-03-24	
International Searching Authority	Signature of Authorized Officer	
Swedish Patent Office	Stig Edhborg	

L.E